

# Durez® 33873

Phenolic

Sumitomo Bakelite North America, Inc.

## Message:

Durez 33873 is a liquid resole phenolic resin in ethanol.

Durez 33873 is recommended for use in the manufacture of friction products; specifically automotive clutch facings.

High strength and temperature resistance.

General Information			
Features	High Heat Resistance		
	High Strength		
Uses	Automotive Applications		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.07	g/cm <sup>3</sup>	Internal Method
pH	8.3		Internal Method
Non-Volatile Content	56	%	Internal Method
Sunshine Gel (121°C)	13.0	min	Internal Method
Thermoset	Nominal Value	Unit	Test Method
Thermoset Mix Viscosity (25°C)	325	cP	Internal Method
Post Cure Time (150°C)	0.013	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

