

Aropol™ A 3058

Thermoset Polyester

Ashland Performance Materials

Message:

Ashland Resins for the Pultrusion Market
Chemistry
High reactivity UPR
Performance Attributes
Good mechanical properties. Excellent surface finish. Excellent processing.
Typical Applications
Parts up to 0.5 in thick. Tool handles. Window lineals. Wastewater components.

General Information		
Features	Good Processability	
	High Reactivity	
	Outstanding Surface Finish	
Uses	Handles	
Processing Method	Pultrusion	
Physical	Nominal Value	Unit
Solution Viscosity	5000	mPa · s
Mechanical	Nominal Value	Unit
Tensile Modulus	3450	MPa
Tensile Strength	58.6	MPa
Tensile Elongation (Break)	2.1	%
Flexural Modulus	3450	MPa
Flexural Strength	101	MPa
Thermal	Nominal Value	Unit
Heat Deflection Temperature	135	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT