

Huafon T31

Polyamide 66
Huafon Group Co., Ltd.

Message:

T3I is light high viscosity resin.
Typical Applications
T31 can be used for spinning coarse denier fibres of high tenacity, primarily for the production of tire cord fabric in automobile, geotextiles in highway construction, conveyor belts, carpets, wool woven bag and so on.

General Information			
Features	High Viscosity		
Uses	Automotive Applications		
	Bags		
	Conveyors		
	Fabrics		
	Fibers		
	Textile Applications		
Processing Method	Fiber (Spinning) Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.14	g/cm ³	ISO 1183
Apparent Density	0.70	g/cm ³	Internal Method
Particle Size	1.40 to 2.00	g/100 pellets	Internal Method
Relative Viscosity	3.10 to 3.20		Internal Method
Water Content	< 800	mg/kg	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT