

# SIBUR Synthetic Rubber DST-30R-01 Group 3

Styrene Butadiene Block Copolymer

SIBUR

Message:

Branched styrene-butadiene thermoplastic elastomer DST-30R-01 is essentially a product of styrene and butadiene block polymerization in hydrocarbon solution in the presence of alkyllithium catalyst.

Product characteristics: Appearance - white to light-beige color; weight - 12kg or 800 kg; packing - cardboard box and soft bag-container (big bag); shelf life - one (1) year since the date of manufacture.

Application

In industries dealing with production of general mechanical rubber goods, ribbon sealants; modification of bituminous roofing materials and plastics; in mastics, protective coatings, shoe compounds.

General Information	
Additive	Oxidation resistance (2000 to 5000 ppm) 2
Features	Antioxidation
	Branched polymer structure
Uses	Protective coating
	Sealant
	Plastic modification
	Footwear
Appearance	White
	Light beige

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	< 1.0	g/10 min	Internal method
Bound Styrene	27.0 - 31.0	%	Internal method
Ash Content		%	Internal method
Volatile Matter		%	Internal method
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	> 72		Internal method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT