

# Ravaflex PIB

Polyisobutylene

Ravago Group

## Message:

Reprocessed polyisobutylene with a very good processibility.

General Information			
Features	Workability, good		
Appearance	Amber		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.920	g/cm <sup>3</sup>	ASTM D297
Mooney Viscosity (ML 1+8, 125°C)	40 - 70	MU	ASTM D1646
Stabilizer - BHT	250 - 500	ppm	
Moisture Content (105°C)		%	Internal method
Ash content-1 hr (550°C)		%	ASTM D297
Packaging	1000	g	
Viscosity Average Molecular Weight	750000 - 2.50E+6		
Additional Information	Nominal Value	Unit	

It shows a good resistance to alkalis, acids and aqueous inorganic salts. It is used in adhesives and in sealing compounds.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

