Duron PBT 30GF

Polybutylene Terephthalate

ProPolymers Inc.

Message:

Duron PBT 30GF is a general purpose 30% glass reinforced PBT that offers a superior combination of mechanical, electrical, and thermal properties. It is lubricated which improves mold release and surface finish. Duron PBT provides outstanding processability and good chemical resistance.

General Information					
Filler / Reinforcement	Glass Fiber,30% Filler by Weight				
Additive	Lubricant				
Features	General Purpose				
	Good Chemical Resistance				
	Good Mold Release				
	Good Processability				
	Good Surface Finish				
	Lubricated				
Uses	General Purpose				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.53	g/cm³	ASTM D792		
Molding Shrinkage			ASTM D955		
Flow : 1.52 mm	0.30 to 0.50	%			
Flow: 3.18 mm	0.50 to 0.80	%			
Across Flow: 1.52 mm	0.40 to 0.60	%			
Across Flow: 3.18 mm	0.60 to 0.90	%			
Water Absorption (24 hr)	0.070	%	ASTM D570		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	118		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	119	MPa	ASTM D638		
Tensile Elongation (Break)	2.8	%	ASTM D638		
Flexural Modulus	7580	MPa	ASTM D790		
Flexural Strength	190	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	90	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load			ASTM D648		
0.45 MPa, Unannealed	222	°C			
1.8 MPa, Unannealed	205	°C			

Melting Temperature	225	°C	
CLTE - Flow	2.0E-5	cm/cm/°C	ASTM D696

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

