

# EEC LLD 3505 U

Polyethylene  
Egyptian European Company

Message:

PCC LLD 3505 U is a Polyethylene product. It can be processed by rotational molding and is available in Africa & Middle East or Europe. Applications of PCC LLD 3505 U include consumer goods, containers, household applications and tanks.

Characteristics include:

Good UV Resistance  
UV Stabilized

General Information			
Additive	UV Stabilizer		
Features	Good UV Resistance		
	Low Density		
Uses	Containers		
	Lawn and Garden Equipment		
	Tanks		
	Toys		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.935	g/cm <sup>3</sup>	ISO 1872-1
Apparent Density	0.37	g/cm <sup>3</sup>	ASTM D1895
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance (23°C, F50)	> 300	hr	ASTM D1693
Particle Size - Medium	< 500	µm	ASTM D1921
Fluidity <sup>1</sup>	31.0	sec	ASTM D1895
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	18.0	MPa	ISO 527-2
Tensile Strain (Break)	700	%	ISO 527-2
Flexural Modulus	724	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	20	kJ/m <sup>2</sup>	ISO 179
NOTE			
1.	Method A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT