

PETILEN H2-21T

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN H2-21T is a Low Density Polyethylene product. It can be processed by film extrusion, sheet extrusion, or wire & cable extrusion and is available in Asia Pacific, Europe, or North America. Applications of PETILEN H2-21T include wire & cable, film and sheet.

General Information			
Uses	Cable Jacketing		
	Film		
	Sheet		
	Wire & Cable Applications		
Forms	Pellets		
Processing Method	Film Extrusion		
	Sheet Extrusion		
	Wire & Cable Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.919 to 0.923	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.1 to 2.9	g/10 min	ASTM D1238
Optical	Nominal Value	Unit	Test Method
Gloss	66		ASTM D2457
Haze	6.6	%	ASTM D1003
Additional Information	Nominal Value		
Film Quality ¹	A		
NOTE			
1.	ALKATHENE 36		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT