

Manner Flexible PVC X4260

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

For the extruded profile and tubing industries, Manner has developed a broad line of products which include low, medium, and high specific gravity materials as well as FDA and NSF recognized compounds. A general purpose transparent offering excellent clarity is also available. The table below shows some of our most popular compounds, but is not a comprehensive view of the Manner Plastics product portfolio. If you do not see a compound offering the performance your application requires, please contact us. We may already have a custom formulation that meets your needs.

General Information			
Features	Good Flexibility High Clarity		
Uses	Profiles Tubing		
Appearance	Opaque		
Forms	Pellets		
Processing Method	Extrusion Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.25	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	60		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	4.48	MPa	ASTM D638
Tensile Strength (Yield)	9.65	MPa	ASTM D638
Tensile Elongation (Break)	440	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-43.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT