

Fluon® PTFE G192

Polytetrafluoroethylene

Asahi Glass Co., Ltd.

Message:

Fluon® PTFE granular powders (moulding powders) are used for the production of sheets, rods, billets and other general mouldings. Filled compounds are described in other page.

Applications:

large billet(300-1,500mm height) sheet moulding. feed stock.

Characteristics:

fine particle powders.

high tensile strength

excellent surface finish.

higher bulk density for G190 and G192.

General Information			
Features	High Strength		
	Outstanding Surface Finish		
Uses	Sheet		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.46	g/cm ³	JIS K6891
Molding Shrinkage	4.7	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	41.0	MPa	JIS K6891
Tensile Elongation (Break)	360	%	JIS K6891
Additional Information	Nominal Value	Unit	Test Method
Median Particle Size	25.0	µm	ASTM D1457
Injection	Nominal Value	Unit	
Injection Pressure	16.0	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT