

KRATON® D2109 DS-W

Styrene Butadiene Styrene Block Copolymer

Kraton Polymers LLC

Message:

Kraton D2109 DS-W is an easy processing, general purpose 45 Shore A hardness material designed for a wide variety of applications. It is supplied from North America in the physical form identified below.

Kraton D2109 DS-W - supplied as a dense, white pellet

General Information	
Features	General Purpose
	Good Processability
	Recyclable Material
Uses	General Purpose
Appearance	White
Forms	Pellets
Processing Method	Extrusion
	Injection Molding
	Thermoforming

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.915 to 0.945	g/cm ³	Internal Method
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	14 to 24	g/10 min	ASTM D1238
Molding Shrinkage - Flow	2.5 to 2.7	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, Compression Molded)	40 to 50		Internal Method
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress ¹			ASTM D412
Across Flow : 100% Strain	1.03	MPa	
Flow : 100% Strain	1.38	MPa	
Across Flow : 300% Strain	1.72	MPa	
Flow : 300% Strain	2.07	MPa	
Tensile Strength ²			ASTM D412
Across Flow : Yield	4.83	MPa	
Flow : Yield	3.45	MPa	
Tensile Elongation ³			ASTM D412
Across Flow : Break	800	%	
Flow : Break	550	%	
Tear Strength ⁴			ASTM D624
Across Flow	26.3	kN/m	


Flow	21.9	kN/m
Injection	Nominal Value	Unit
Rear Temperature	171 to 182	°C
Front Temperature	188 to 199	°C
Nozzle Temperature	177 to 193	°C
Mold Temperature	10.0 to 37.8	°C
Injection Pressure	3.45 to 4.83	MPa
Injection Rate	Moderate-Fast	
Back Pressure	0.276 to 0.414	MPa
NOTE		
1.	Die C	
2.	Die C	
3.	Die C	
4.	Die C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
 Phone: +86 13424755533
 Email: sales@su-jiao.com
 No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT