

# DJSilicone NE-8135

Silicone

DONGJUE SILICONE (NANJING) CO., LTD

Message:

With better tensile strength, elongation and tear strength than common and general silion rubber, high-strength silicone rubber for molding is suitable for molding products with higher mechanical property requirements.

General Information			
Features	High Strength		
Appearance	Translucent		
	White		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.05 to 1.15	g/cm <sup>3</sup>	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	33 to 37		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Set	< 6	%	ASTM D412
Tensile Strength (Yield)	> 6.50	MPa	ASTM D412
Tensile Elongation (Break)	> 550	%	ASTM D412
Tear Strength	> 17.0	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT