

EnviroPro 2010TF40

Polypropylene Copolymer

West Michigan Compounding

Message:

EnviroPro 2010TF40 is a polypropylene copolymer (PP Copoly) product, which contains 40% talc filler. It is available in North America.

Features include:

High stiffness

Copolymer

General Information			
Filler / Reinforcement	Talc filler, 40% filler by weight		
Features	Rigidity, high		
	Copolymer		
	General		
Uses	General		
Appearance	Black		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.60 - 1.1	%	ASTM D955
Ash Content	40	%	ASTM D5630
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	22.1	MPa	ASTM D638
Tensile Elongation (Break)	16	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	53	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT