Huafon JF-W-AL6090

Polyurethane

Huafon Group Co., Ltd.

Message:

Wet Process Resin with Hydrolysis Resistance for Action Leather

Characteristics

Mid hard type, 24 hours hydrolysis resistance, good film thickness, good embossing property.

Applications

Shoes

| General Information | | | |
|-------------------------------|----------------------|------|--|
| Features | Hydrolysis Resistant | | |
| | Medium Hardness | | |
| Uses | Footwear | | |
| Additional Information | Nominal Value | Unit | |
| Solvents | DMF | | |
| Uncured Properties | Nominal Value | Unit | |
| Solids Content | 29 to 31 | % | |
| Viscosity (25°C) | 220 to 280 | Pa·s | |
| Cured Properties | Nominal Value | Unit | |
| Tensile Modulus (100% Secant) | 7.00 to 9.00 | MPa | |
| Tensile Strength | > 15.0 | MPa | |
| Tensile Elongation at Break | > 400 | % | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

