

# ResinDirect HIPS8

High Impact Polystyrene

ResinDirect

Message:

ResinDirect HIPS8 is a High Impact Polystyrene material. It is available in North America.

Important attributes of ResinDirect HIPS8 are:

Flame Rated

Impact Resistant

General Information			
Features	General Purpose		
	High Impact Resistance		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Yield)	24.1	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Yield)	40	%	ASTM D638
Flexural Modulus <sup>3</sup>	1790	MPa	ASTM D790
Flexural Strength <sup>4</sup>	34.5	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (3.18 mm)	130	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	82.2	°C	ASTM D648
Vicat Softening Temperature	97.8	°C	ASTM D1525 <sup>5</sup>
Flammability	Nominal Value	Test Method	
Flame Rating	HB	UL 94	
NOTE			
1.	5.1 mm/min		
2.	5.1 mm/min		
3.	2.5 mm/min		
4.	2.5 mm/min		
5.	Rate B (120°C/h)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

