

# Kumho PPG 3600

Polyolefin Plastomer

Korea Kumho Petrochemical Co., Ltd.

## Message:

PPG 3600 is a nominal 3800 molecular weight blended POP and triol based on propylene oxide and ethylene oxide. It well suited to use in the production of high loadbearing purpose flexible polyurethane slabstock foams and other application.

General Information		
Forms	Liquid	
Physical	Nominal Value	Unit
Acid Number	< 0.10	Mg/g
Molecular Weight	3500 to 4000	
pH <sup>1</sup>	6.5 to 8.5	
Solids Content	10	%
Viscosity (25°C)	675 to 925	mPa·s
Water Content	< 0.10	%
Hydroxyl Value	42.0 to 46.0	Mg/g
NOTE		
1.	1H20/10MeOH	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

