

HIVAL® 106033

Linear Low Density Polyethylene
Nexeo Solutions, LLC.

Message:

HIVAL® 106033 is a Linear Low Density Polyethylene material. It is available in North America for rotational molding.
Important attributes of HIVAL® 106033 are:
Antioxidant
Good UV Resistance
Hexene Comonomer
UV Stabilized

General Information			
Additive	Antioxidant		
	UV Stabilizer		
Features	Antioxidant		
	Good UV Resistance		
	Hexene Comonomer		
Uses	General Purpose		
Forms	Pellets		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.935	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0	g/10 min	ASTM D1238
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	530	J/m	ASTM D256
Tensile Impact Strength	164	kJ/m²	ASTM D1822
Thermal	Nominal Value	Unit	
Melting Temperature	128	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT