

Capran® UNIDRAW 102

Polyamide 6

Honeywell

Message:

Capran® UNIDRAW 102 is a Polyamide 6 (Nylon 6) product. It is available in North America. Applications of Capran® UNIDRAW 102 include coating applications and film. Primary characteristic: high strength.

General Information			
Features	High Strength		
Uses	Laminates		
	Oriented Film		
Forms	Film		
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	µm	
Secant Modulus			ASTM D882
1% Secant, MD	2410	MPa	
1% Secant, TD	2550	MPa	
Tensile Strength			ASTM D882
MD : Yield	310	MPa	
TD : Yield	75.8	MPa	
Tensile Elongation			ASTM D882
MD : Break	75	%	
TD : Break	330	%	
Elmendorf Tear Strength			ASTM D1922
MD	40	g	
TD	120	g	
Optical	Nominal Value	Unit	Test Method
Haze	3.5	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT