

HANWHA P-700

Polyvinyl Chloride

Hanwha Chemical

Message:

Feature: Easy processing due to its low temperature melting characteristic and high liquidity/ good for injection mold products

Use: General hard sheets, bottle, fitting and injection mould

General Information			
Features	Good Processability		
Uses	Bottles		
	Fittings		
	Sheet		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.52 to 0.60	g/cm ³	ASTM D1895
Particle Size - 42Mesh(350µm) Sieve Pass %	100	%	Internal Method
Volatile Matter	< 0.30	%	ASTM D3030
Degree of Polymerization			
DP	650 to 750		JIS K6720-2
K-Value	58.0		DIN 53726

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

