

Shin-Etsu Elastomer KE-581U

Silicone Rubber, HTV

Shin-Etsu Silicones of America

Message:

KE-581U is one of a series of easy processing, general purpose grade silicone rubber bases. It can be used in a variety of applications requiring finishing by molding or extruding with extending filler.

This product can be blended with KE-541U, KE-551U, KE-561U, and KE-571U for intermediate hardnesses. The choice between these bases will depend on specific requirements.

Typical Applications

Roll covers.

Diaphragms.

O-rings and gaskets.

General Information		
Features	Workability, good	
	General	
Uses	Washer	
	Diaphragm	
	General	
Processing Method	Extrusion	
	Injection molding	
Physical	Nominal Value	Unit
Specific Gravity	1.24	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness	78	
Elastomers	Nominal Value	Unit
Tensile Strength	11.2	MPa
Tensile Elongation (Break)	350	%
Tear Strength ¹	12.1	kN/m
Compression Set (150°C, 22 hr)	23	%
Additional Information	Nominal Value	
Cure Agent	DCBP	
Press / Post Cure: Post		
NOTE		
1.	B mould	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

