

# Europrene® HS 630

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

## Message:

Europrene® HS 630 is a resin rubber masterbatch obtained by coagulating with acid a blend of a high styrene resin latex and a SBR latex.

It is made at the Ravenna production facility in Italy.

A non-staining antioxidant is added during the production process.

### Key Features

Europrene® HS 630, a self reinforcing SBR, is used in blends with general purpose rubbers to obtain high hardness, high modulus and improved abrasion resistance.

### Main Applications

Footwear, flooring, sheeting, hoses and technical goods.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Good Abrasion Resistance		
	High Hardness		
Uses	Blending		
	Flooring		
	Footwear		
	Hose		
	Masterbatch		
	Sheet		
Forms	Flakes		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 100°C)	56	MU	ASTM D1646
Bound Styrene	63.0	%	ASTM D5775
Ash Content	< 0.4	wt%	ASTM D5667
Organic Acid	5.0	wt%	ASTM D5774
Soap	< 0.3	wt%	ASTM D5774
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

