Hanwha Total PE E220F

Ethylene Vinyl Acetate Copolymer

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

E220F is a EVA (ethylene-vinylacetate copolymer) resin for crosslinked foam applications including mid-sole and in-sole of athletic shoes. This grade is designed to be processed in conventional kneading and rolling equipment for mixing and dispersing crosslinking agent and foaming agent.

General Information				
Features	Low compressive deformability			
	Copolymer			
	Dispersible			
	Workability, good			
	Crosslinkable			
	Good tear strength			
llees	Electronic insulation			
Uses				
	Composite			
	Foam			
	Footwear			
Forms	Particle			
Processing Method	Composite			
	Compression molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.944	g/cm ³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.0	g/10 min	ASTM D1238	
Environmental Stress-Cracking Resistance (50°C, F10)	500	hr	ASTM D1693	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shaw A	90		ASTM D2240	
Shaw D	35		ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method	
Mechanical Tensile Strength (Break)	Nominal Value 28.4	Unit MPa	Test Method ASTM D638	
Tensile Strength (Break)	28.4	MPa	ASTM D638	
Tensile Strength (Break) Tensile Elongation (Break)	28.4 800	MPa %	ASTM D638 ASTM D638	
Tensile Strength (Break) Tensile Elongation (Break) Apparent Bending Modulus	28.4 800 44.1	MPa % MPa	ASTM D638 ASTM D638 ASTM D747	

Melting Temperature	87.0	°C	

Additional Information

Kneader Temperature: 95 to 105 °CFoaming Temperature: 155 °CFoaming Pressure: 150 kg/cm³Curing Time: 40 minVA Content, SAMSUNG TOTAL: 22 kg force/cm²

NOTE

压力1 (10N)

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

