# ADMER™ QF500A

## Polypropylene

Mitsui Chemicals America, Inc.

#### Message:

ADMER™ QF500A is a Polypropylene material. It is available in North America for blown film or cast film. Typical applications include:

Adhesives/Tapes

Sheet

| General Information             |               |          |             |
|---------------------------------|---------------|----------|-------------|
| Uses                            | Adhesives     |          |             |
|                                 | Sheet         |          |             |
|                                 |               |          |             |
| Forms                           | Pellets       |          |             |
| Processing Method               | Blown Film    |          |             |
|                                 | Cast Film     |          |             |
|                                 |               |          |             |
| Physical                        | Nominal Value | Unit     | Test Method |
| Density                         | 0.900         | g/cm³    | ASTM D1505  |
| Melt Mass-Flow Rate (MFR) (230° | C/2.16        |          |             |
| kg)                             | 3.0           | g/10 min | ASTM D1238  |
| Thermal                         | Nominal Value | Unit     | Test Method |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

°C

ASTM D1525

### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

143

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Vicat Softening Temperature

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

