

TechnoElast V A9000 I 2 sw

Thermoplastic Elastomer
TechnoCompound GmbH

Message:
Good insulation, absorption and elastic properties

| General Information | | | |
|-------------------------------------|------------------|-------|--------------|
| Appearance | Black | | |
| | Available colors | | |
| | Natural color | | |
| Physical | Nominal Value | Unit | Test Method |
| Density (23°C) | 0.970 | g/cm³ | ISO 1183 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 3 sec) | 90 | | DIN 53505 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress | | | |
| Fracture | 8.20 | MPa | ISO 527-2/1 |
| 100% strain | 6.10 | MPa | ISO 527-2/50 |
| Tensile Strain (Break) | 440 | % | ISO 527-2/50 |
| Elastomers | Nominal Value | Unit | Test Method |
| Compression Set (70°C, 22 hr) | 38 | % | ISO 815 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT