Hanwha Total PP SI83R

Polypropylene

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

SI83R is a high-gloss polypropylene compound specially processed for high-flowability and low deformation. TOTAL engineering has resulted in impressively improved grades that are far superior to the low gloss, low productivity and high-warp characteristics extant in other brands. This grade is also designed for application on exterior parts of large home appliances, such as rectangular rice cooker housings.

General Information				
UL YellowCard	E140331-222953			
Features	Crystalline			
	Good Thermal Stability			
	High Flow			
	High Gloss			
	High Heat Resistance			
	High Impact Resistance			
	High Rigidity			
	Isophthalic			
	Low Warpage			
Uses	Appliances			
	Household Goods			
	Housings			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.10	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	50	g/10 min	ASTM D1238	
Molding Shrinkage - Flow (2.00 mm)	1.1 to 1.3	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	105		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ¹ (Yield)	36.3	MPa	ASTM D638	
Tensile Elongation ² (Break)	50	%	ASTM D638	
Flexural Modulus ³	2350	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	39	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	

Deflection Temperature Under Lo	oad (0.45		
MPa, Unannealed)	133	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94
NOTE			
1.	50 mm/min		
2.	50 mm/min		
3.	5.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

