

Durez® 31403

Phenolic

SBHPP

Message:

Durez® 31403 is a finely pulverized novolak-hexa mixture. Durez® 31403 can be used as a binder system in the production of laminates, cotton paddings and friction materials.

General Information			
Uses	Laminate		
	Adhesive		
Appearance	Light brown		
Forms	Powder		
Thermal	Nominal Value	Unit	Test Method
Melting Temperature ¹	100	°C	Internal method
Additional Information	Nominal Value	Unit	Test Method
Inclined Plate Flow - 0.5 g (125°C)	3.60	cm	Internal method
Screen Mesh - 200 mesh	0.80	%	Internal method
Uncured Properties	Nominal Value	Unit	Test Method
Curing Time (165°C)	0.010	hr	Internal method
NOTE			
1.	Clear		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT