

Daelim Po1y® TR-420

High Density Polyethylene

DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y® TR-420 is a High Density Polyethylene product. It can be processed by profile extrusion and is available in Asia Pacific. Applications of Daelim Po1y® TR-420 include plumbing/piping/potable water and wire & cable.

Characteristics include:

Good Processability

High Stiffness

Impact Resistant

General Information			
Features	Good Processability		
	High Stiffness		
	Ultra High Impact Resistance		
Uses	Piping		
	Telecommunications		
Agency Ratings	ASTM D 1248, III, Class A, Cat. 5		
Forms	Pellets		
Processing Method	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.949	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.16	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	25.5	MPa	ASTM D638
Tensile Elongation (Break)	> 600	%	ASTM D638
Flexural Modulus	981	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 6.00 mm)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	126	°C	ASTM D1525
Oxidation Induction Time ² (200°C)	> 40	min	ASTM D3895
Extrusion	Nominal Value	Unit	
Melt Temperature	190 to 220	°C	
NOTE			
1.	50 mm/min		
2.	AI Pan		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

