

Verolloy A1300

Acrylonitrile Butadiene Styrene + Nylon

PlastxWorld Inc.

Message:

Verolloy A1300 is an Acrylonitrile Butadiene Styrene + Nylon (ABS+Nylon) product. It is available in Europe or North America.

Characteristics include:

- Flame Rated
- High Strength
- Impact Resistant

General Information				
UL YellowCard		E315545-100091178		
Features		High Impact Resistance		
		High Tensile Strength		
Forms		Pellets		
Physical	Dry	Conditioned	Unit	Test Method
Specific Gravity	1.04	--	g/cm ³	ASTM D792
Water Absorption (24 hr)	0.50	--	%	ASTM D570
Mechanical	Dry	Conditioned	Unit	Test Method
Tensile Strength (Break)	40.7	32.4	MPa	ASTM D638
Flexural Modulus	2000	1500	MPa	ASTM D790
Flexural Strength	60.0	44.8	MPa	ASTM D790
Impact	Dry	Conditioned	Unit	Test Method
Notched Izod Impact				ASTM D256
--	--	320	J/m	
23°C, 3.18 mm	320	--	J/m	
Thermal	Dry	Conditioned	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)				
	90.0	82.2	°C	ASTM D648
Vicat Softening Temperature				
	90.0	--	°C	ASTM D1525
Flammability	Dry	Conditioned	Test Method	
Flame Rating (1.50 mm)	HB	--	UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

