

POLIMAXX V7030J

Low Density Polyethylene
IRPC Public Company Limited

Message:
POLIMAXX V7030J is a Low Density Polyethylene product. It is available in Asia Pacific, Europe, or North America. Typical application: Foam. Primary characteristic: good processability.

General Information			
Features	Good Processability		
Uses	Foam		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.945	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	9.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	22.0	MPa	
Break	10.5	MPa	
Tensile Elongation (Break)	72	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	111	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT