

Braskem PP C719-35RNHP

Polypropylene Impact Copolymer

Braskem America Inc.

Message:

Sub-group
Impact Copolymer
Description
High impact, contains nucleating agent, controlled rheology product
Applications
Suggested uses include injection molding applications requiring good impact/stiffness balance, compounding

General Information			
Additive	Nucleating Agent		
Features	Controlled Rheology		
	Food Contact Acceptable		
	High Impact Resistance		
	Impact Copolymer		
	Nucleated		
Uses	Compounding		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	35	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	20.7	MPa	ASTM D638
Tensile Elongation ² (Yield)	5.0	%	ASTM D638
Flexural Modulus - 1% Secant ³	1070	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	190	J/m	ASTM D256A
NOTE			
1.	51 mm/min		
2.	51 mm/min		
3.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

