

NEOFLON™ RP-4020

Fluoropolymer

Daikin Fluorochemicals (China) Co., Ltd.

Message:

NEOFLON EFEP is a new fluoropolymer that has the ability to adhere with other materials, different from existing non-adhesive fluoropolymer. Moreover, it has the same chemical resistance as other types of fluoropolymers. Specific gravity is approximately 1.75. A laminated product such as a multi-layer tube and film can be obtained with co-extrusion molding.

It is more transparent than conventional fluoropolymers and is the next generation material to expand the possibilities of fluoropolymer application.

Features

Adherable to other plastics and excellent transparency. Suitable for tubes.

General Information		
Features	Good Adhesion	
	High Clarity	
Uses	Multilayer Film	
	Tubing	
Appearance	Clear/Transparent	
Processing Method	Coextrusion	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	25 to 50	g/10 min
Thermal	Nominal Value	Unit
Melting Temperature	155 to 170	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT