

Tecnoflon® FOR 7352

Fluoroelastomer
Solvay Specialty Polymers

Message:

TECNOFLON® FOR 7352 is a medium-low viscosity cure incorporated fluoroelastomer copolymer. TECNOFLON® FOR 7352 is well suited for applications where excellent compression set and superior mold release are required.

Some of the basic properties of Tecnoflon® FOR 7352 are:

- Very good scorch safety
- Good mold flow
- Excellent mold release
- Lack of mold fouling

TECNOFLON® FOR 7352 can be used for compression and transfer moulding of O-rings, gaskets, and seals. The product can be mixed using typical fluoroelastomers compounding ingredients and mixing can be accomplished with two-roll mills or internal mixers.

The material can be extruded into hoses or profiles and can be calendered to make sheet stocks or belting. Finished goods can be produced by a variety of rubber processing methods.

General Information		
Features	Copolymer	
	Good Flow	
	Good Mold Release	
	Low Compression Set	
	Medium-low Viscosity	
Uses	Belts/Belt Repair	
	Gaskets	
	Hose	
	Profiles	
	Seals	
	Sheet	
Appearance	Off-White	
Forms	Slab	
Processing Method	Calendering	
	Compounding	
	Compression Molding	
	Extrusion	
	Resin Transfer Molding	
Physical	Nominal Value	Unit
Mooney Viscosity ¹ (ML 1+10, 121°C)	41	MU
Fluorine Content ²	66	%
NOTE		
1.	Raw polymer	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

