

# ICORENE® 2550

Linear Low Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

## Message:

ICORENE® 2550 is a linear low density polyethylene powder specically developed for rotational moulding.

The ICORENE® 2550 has been designed for applications requiring good processability, toughness and flexibility. This grade is suitable or use in many different applications.

General Information			
Additive	UV Stabilizer		
Features	Good Flexibility		
	Good Processability		
	Good Toughness		
	Good UV Resistance		
Uses	Flotation Devices		
	Furniture		
	Outdoor Furnishings		
Appearance	Natural Color		
	Unspecified Color		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.6	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	13.0	MPa	ASTM D638
Tensile Elongation (Break)	> 1000	%	ASTM D638
Flexural Modulus	308	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Drop Impact Resistance <sup>1</sup> (-20°C)	200	J/cm	Internal Method
NOTE			
1.	Based on ISO 6603		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

