

Westlake PVC 1195B

Polyvinyl Chloride

Westlake Chemical Corporation

Message:

Westlake PVC 1195 PVC resin is a low molecular weight resin designed for rigid injection molding, calendering, sheet extrusion, and blow molding.

Suggested Applications

Westlake PVC 1195 PVC resin is well suited for a broad range of applications. Typical applications include pipe fittings and other injection molded products, calendered film and sheet, extruded sheet, bottles, and plasticized applications.

General Information	
Additive	Plasticizer
Features	Low Molecular Weight Plasticized
Uses	Bottles Film Piping Sheet
Appearance	White
Forms	Powder
Processing Method	Blow Molding Calendering Film Extrusion Injection Molding Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.53	g/cm ³	ASTM D1895
K-Value	58.0		
Inherent Viscosity	0.73		ASTM D5225
Particle Size			ASTM D1921
-- 1	> 99.9	%	
-- 2	< 7.00	%	
Relative Viscosity	1.90		
ASTM Classification	GP2-16050		ASTM D1755
Volatiles	< 0.20	%	

NOTE	
1.	Through 40 mesh
2.	Through 200 mesh

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

