Moplen H500J

Polypropylene Homopolymer

Shazand (Arak) Petrochemical Corporation

Message:

Flexural Modulus

Oven Aging (150°C)

Notched Izod Impact (23°C)

Impact

Moplen HP500J is a polypropylene homo-polymer for injection moulding applications. Moplen HP500J combines high stiffness & fairly good impact strength with good process ability. The grade is suitable for a wide range of applications such as house wares, caps, closures, small containers, toys ,parts for small appliances & components for the automotive industry. Moplen HP500J is also used for compounding.

^{*} Moplen HP500J is suitable for food contact.

General Information					
Features	Food Contact Acceptable				
	Good Impact Resistance				
	Good Processability				
	High Stiffness				
	Homopolymer				
Uses	Appliance Components				
	Automotive Applications				
	Caps				
	Closures				
	Compounding				
	Containers				
	Household Goods				
	Toys				
D : M. I					
Processing Method	Compounding				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	3.0	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	102		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	35.0	MPa	ASTM D638		
Tensile Elongation (Yield)	12	%	ASTM D638		

MPa

Unit

J/m

Unit

day

ASTM D790

Test Method

ASTM D256

Test Method

ASTM D3012

1350

35

15.0

Nominal Value

Nominal Value

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45		
MPa, Unannealed)	94.0	°C	ASTM D648
Vicat Softening Temperature	156	°C	ASTM D1525 ¹
NOTE			
1.	Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

