Daelim Po1y® PP-333J

Polypropylene Random Copolymer DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y®PP-333J is a polypropylene random copolymer (PP random copolymer) product. It can be processed by injection molding and is available in the Asia-Pacific region. Daelim Po1y®PP-333J application areas include home applications and containers.

Features include:

high gloss Copolymer Good processability accessible food Rapid Prototyping Cycle

General Information					
Features	Highlight				
	Workability, good				
	Fast molding cycle				
	Definition, high				
	Compliance of Food Exposure				
	Random copolymer				
	Excellent appearance				
Uses	Household goods				
	Food container				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	5 24	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	110		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	27.5	MPa	ASTM D638		
Tensile Elongation (Yield)	20	%	ASTM D638		
Flexural Modulus	1180	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	29	J/m	ASTM D256		
23°C	49	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		

Deflection Temperature Under Load (0.45				
MPa, Unannealed)	130	°C	ASTM D648	
Vicat Softening Temperature	85.0	°C	ASTM D1525	
Optical	Nominal Value	Unit	Test Method	
Optical Haze	Nominal Value	Unit %	Test Method ASTM D1003	

Accelerated Oven Aging in Air, ASTM D3012, Forced Circulation at 150°C: 360 hours

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

