

# Sylvin 6920X08 Orange 5123

Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:  
Sylvin 6920X08 Orange 5123 is a polyvinyl chloride material. This product is available in North America and is processed by extrusion.  
The typical application fields of Sylvin 6920X08 Orange 5123 are: architectural applications

General Information			
Uses	Building materials		
	Architectural application field		
Appearance	Orange		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.37	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	86		ASTM D2240
Shaw A, 10 seconds	86		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	16.5	MPa	ASTM D638
Tensile Elongation (Break)	340	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	74.4	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT