

Europrene® SOL R 72614

Solution Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene® SOL R 72614 is a solution polymerized, oil extended styrene-butadiene random copolymer.

The polymer is extended with a TDAE oil and contains a non-staining antioxidant.

It is produced by batch polymerization process at the Grangemouth production facility in Scotland, UK.

Key Features

Europrene® SOL R 72614 has a microstructure and a molecular weight distribution designed to show a good trade-off between processability and final properties.

Main Applications

Silica - based compounds for low rolling resistance tyre treads.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Random Copolymer		
Uses	Compounding		
Forms	Bale		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 100°C)	55	MU	ASTM D1646
Bound Styrene	25.0	%	ASTM D5775
Oil Type (TDAE Oil)	37.5	phr	ASTM D5774
Ash Content	< 0.2	wt%	ASTM D5667
Vinyl Content ¹	64.0	wt%	Internal Method
Volatile Matter	< 0.75	wt%	ASTM D5668
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-30.0	°C	Internal Method
NOTE			

1. Referred to butadiene portion

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT