

DOWLEX™ 2048G

Linear Low Density Polyethylene Resin
The Dow Chemical Company

Message:

Linear Low Density Polyethylene.
For high performance form-fill-seal packaging applications.
Outstanding tear strength, impact strength and toughness.
Formulated with slip and antiblock additives.
Complies with U.S. FDA 21 CFR 177.1520 (c) 3.1a.
Consult the regulations for complete details.


General Information			
Additive	Antiblock (3000 ppm)		
	Slip (1200 ppm)		
Agency Ratings	FDA 21 CFR 177.1520(c) 3.1a		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.919	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.3	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT