

ETILGUM ME/0 P2Z

Thermoplastic Elastomer

Crosspolimeri S.p.A.

Message:

ETILGUM ME/0 P2Z is a modified rubber technopolymer presenting many of the positive features of pure rubbers and plastic materials: lead free. ETILGUM ME/0 P2Z presents good deformation and compression resistance and has a good resistance properties to flex-fatigue and to abrasion. Also good resistance to the fuels.

General Information			
Features	Fatigue Resistant		
	Fuel Resistant		
	Good Abrasion Resistance		
	Low (to None) Lead Content		
Uses	Wire & Cable Applications		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	50		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	12.0	MPa	ASTM D638
Tensile Elongation (Break)	380	%	ASTM D638
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	140	°C	
Cylinder Zone 2 Temp.	145	°C	
Cylinder Zone 3 Temp.	150	°C	
Cylinder Zone 4 Temp.	155	°C	
Cylinder Zone 5 Temp.	165	°C	
Die Temperature	170	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT