

KEP® 020P

Ethylene Propylene Copolymer

Kumho Polychem Co., Ltd.

Message:

Features:

Low mooney viscosity & high MFR & high gloss, excellent low temperature flexibility in the modification of polyolefin thermoplastics (PP, PE)

Applications:

Blend with PP: TPO, sponge, films, sheets, automotive applications (bumper, spoiler, instrument panel)

Blend with PE: films

General Information		
Features	Good Flow	
	High Gloss	
	Low Temperature Flexibility	
Uses	Automotive Applications	
	Automotive Bumper	
	Automotive Instrument Panel	
	Blending	
Forms	Pellets	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+4, 100°C)	25	MU
Ethylene Content	71.0	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

