

Complet® LCF30-PPS

Polyphenylene Sulfide

PlastiComp, Inc.

Message:

Complet® LCF30-PPS is a Polyphenylene Sulfide (PPS) product filled with 30% long carbon fiber. It is available in Asia Pacific, Europe, or North America. Primary characteristic: rohs compliant.

General Information			
Filler / Reinforcement	Long Carbon Fiber,30% Filler by Weight		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.45	g/cm ³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	33800	MPa	ASTM D638
Tensile Strength	187	MPa	ASTM D638
Tensile Elongation (Break)	0.70	%	ASTM D638
Flexural Modulus	25500	MPa	ASTM D790
Flexural Strength	296	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact	460	J/m	ASTM D4812

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

