DJSilicone NE-5160

Silicone

DONGJUE SILICONE (NANJING) CO., LTD

Message:

This product has good physical and mechanical properties, and is suitable for making common keypads, silicone rubber products and accessories, especially for colored rubber products and molding process.

| General Information | | | |
|------------------------------|-------------------|-------|-------------|
| Features | Good Colorability | | |
| Appearance | Light Grey | | |
| | White | | |
| | Yellow | | |
| | | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 1.13 to 1.23 | g/cm³ | ASTM D1505 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A) | 57 to 63 | | ASTM D2240 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Set | < 10 | % | ASTM D412 |
| Tensile Strength (Yield) | > 7.00 | MPa | ASTM D412 |
| Tensile Elongation (Break) | > 280 | % | ASTM D412 |
| Tear Strength | > 18.0 | kN/m | ASTM D624 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

