YUPLENE® R390Y

Polypropylene Random Copolymer

SK Global Chemical

Message:

YUPLENE R390Y is random polypropylene that is made for injection molding. It has high impact strength and excellent transparency. Since Its excellent flow property makes it suitable for various large size home appliances and thin wall products. It can be used for food packaging, packaging container, and various home appliances.

YUPLENE R390Y complies with FDA regulation in 21 CFR 177.1520 and 21 CFR 178.2010 for food packaging substances.

General Information					
Features	Food Contact Acceptable				
	Good Flow				
	High Impact Resistance				
	Random Copolymer				
Uses	Appliances				
	Containers				
	Food Packaging				
	Household Goods				
	Packaging				
	Thin-walled Parts				
	Transparent or Translucent Parts				
Agency Ratings	FDA 21 CFR 177.1520				
	FDA 21 CFR 178.2010				
Appearance	Clear/Transparent				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	45	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	85		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	29.4	MPa	ASTM D638		
Tensile Elongation (Break)	> 500	%	ASTM D638		
Flexural Modulus	1180	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	59	J/m	ASTM D256		
Aging	Nominal Value	Unit	Test Method		
Oven Aging - in Air (150°C)	15.0	day	ASTM D3012		

Heat Deflection Temperature	95	°C	ASTM D648
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	130	°C	ASTM D1525
Optical	Nominal Value	Unit	Test Method
Haze (1000 μm)	6.0	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

