

Fixmaster Fast Set Grout

Epoxy; Epoxide

Loctite®

Message:

Fixmaster Fast Set Grout is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Typical application: Construction Applications.

Characteristics include:

Chemical Resistant

Corrosion Resistant

Low Shrinkage

General Information			
Features	Good Chemical Resistance		
	Good Corrosion Resistance		
	Low Shrinkage		
Uses	Flooring Maintenance/Repair		
Appearance	Red		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	28.3	MPa	ASTM D638
Compressive Strength	114	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	15	min	
Demold Time (25°C)	480 to 720	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

