

Thermoset Plastics SC-104

Silicone

Thermoset, Lord Chemical Products

Message:

Thermoset Plastics SC-104 is a Silicone material. It is available in North America for casting or encapsulating.

Important attributes of Thermoset Plastics SC-104 are:

Flame Rated

Conductive

Insulating

Typical application of Thermoset Plastics SC-104: Wire & Cable

General Information	
UL YellowCard	E84716-251647
Features	Electrically Insulating
	Thermally Conductive
Uses	Electronic Insulation
Appearance	Grey
Forms	Pellets
Processing Method	Casting
	Encapsulating

Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.09	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	67		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	3.31	MPa	ASTM D638
Tensile Elongation (Yield)	120	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Thermal Conductivity	0.85	W/m/K	ASTM C177
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	2.2E+15	ohms · cm	ASTM D257
Dielectric Constant			ASTM D150
	100 Hz	3.10	
	100 kHz	3.06	
Dissipation Factor			ASTM D150
	100 Hz	7.5E-3	
	100 kHz	1.8E-3	
Flammability	Nominal Value	Unit	Test Method
Flame Rating	V-0		UL 94
Thermoset	Nominal Value	Unit	Test Method


Thermoset Components			
Hardener	Mix Ratio by Weight: 1.0		
Resin	Mix Ratio by Weight: 1.0		
Thermoset Mix Viscosity (25°C)	7000	cP	ASTM D2393
Demold Time (25°C)	1400	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
 Phone: +86 13424755533
 Email: sales@su-jiao.com
 No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT