

TITANEX® HM1032

High Density Polyethylene

Lotte Chemical Titan (M) Sdn. Bhd.

Message:

TITANEX® HM1032 is a High Density Polyethylene material. It is available in Asia Pacific for extrusion.

Important attributes of TITANEX® HM1032 are:

Butene Comonomer

Good Processability

Heat Resistant

Typical applications include:

Adhesives/Tapes

Yarn

General Information			
Features	Butene Comonomer		
	Good Drawdown		
	Good Processability		
	Good Strength		
	Good Thermal Stability		
	Low Die Swell		
Uses	High Tenacity Flat Yarn		
	Tape		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.954	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.90	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	33.3	MPa	
Break	35.3	MPa	
Tensile Elongation (Break)	900	%	ASTM D638
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	230 to 280	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

