

Viton® VTR-9192

Fluoroelastomer
DuPont Performance Elastomers

Message:

Viton® VTR-9192 is a fluororubber (Fluorelastomer) product. It can be processed by extrusion, resin transfer molding or injection molding, and is available in North America or Europe. Viton® VTR-9192 application areas include hoses and engineering/industrial accessories.

Features include:

- Good processability
- chemical resistance

General Information	
Features	Solvent resistance
	Workability, good
Uses	Washer
	Pipe
	Pipe fittings
Forms	Particle
Processing Method	Extrusion
	Resin transfer molding
	Injection molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.76	g/cm ³	ASTM D792
Elastomers	Nominal Value	Unit	Test Method
Compression Set (200°C, 70 hr)	25	%	ASTM D395

Additional Information			
Nominal Viscosity, ML 1 + 10, 121°C: 32Polymer Fluorine Content: 66%			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT