

# PETILEN I22-19T

Low Density Polyethylene  
PETKIM Petrokimya Holding A.S.

Message:  
PETILEN I22-19T is a Low Density Polyethylene product. It can be processed by injection molding and is available in Asia Pacific, Europe, or North America. Applications of PETILEN I22-19T include caps/lids/closures, additive/masterbatch, consumer goods and kitchenware.

General Information			
Uses	Caps		
	Closures		
	Kitchenware		
	Masterbatch		
	Toys		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.917 to 0.921	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	17 to 29	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT