# Geon™ Vinyl Flexible XV3906

### Flexible Polyvinyl Chloride

### PolyOne Corporation

### Message:

Geon™Vinyl Flexible XV3906 is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon™The application areas of Vinyl Flexible XV3906 include medical/health care and food contact applications.

Features include: accessible food plasticization

NOTE

2.

Features	Non-phthalate plasticizer		
	Compliance of Food Exposure		
Uses	Medical devices		
Agency Ratings	CPSIA Compliant		
	FDA Food Exposure, Not Rated		
	ISO 10993 Part 5		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Extrusion		
	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	75		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup>			ASTM D638
Fracture	17.2	MPa	ASTM D638
100% strain	8.27	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Break)	350	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-35.0	°C	ASTM D746

仅为食品及药物管理局清单关于该产品内容的概述.由用户负责确保此化合物适用于其预期应用.

Type 4, 510mm/min

Type 4, 510mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

